

# Motorized High Lift Wheel Dolly

### **Model SKWD 500/501**

- ▶ Heavy steel framing assembled to the highest industry standards
- Fully hydraulic operation
- Available in your choice of pneumatic or 12 VDC power
- ▶ High quality non-destructive, non-marring nylon wheels
- Swiveling rear wheels for tight turning radius and portability
- Nylon safety strap securely holds wheel assembly in place during removal or reinstallation
- Steel cover for foot protection
- Easily positioned by one technician
- Lifting forks incorporate rollers to allow rotation of wheels for easy bolt pattern alignment during removal and installation
- Lifting forks tilt 10° above and 4° below horizontal for precise alignment
- Use with vehicle at floor level or full lifted height

SKWD 500 shown with optional G-BDA brake drum adapter





**SKWD 501** 

### Ideal for **Dually Wheels!**





## **Specifications**

MODEL	CAPACITY	POWER	LIFTING HEIGHT	SPEED PER MIN.	WHEEL DIAMETER
SKWD 500	1,000 lbs.	Pneumatic	52"	78"	36"–48"
SKWD 500E	1,000 lbs.	12 VDC	52"	78"	36"–48"
SKWD 500D74	1,000 lbs.	Pneumatic	74"	78"	36"–48"
SKWD 500E74	1,000 lbs.	12VDC	74"	78"	36"–48"
SKWD 501*	850 lbs.	Pneumatic	52"	78"	36"–48"

<sup>\*</sup> Counterbalance design for use with platform lifts only.

#### Contact Carl Boyer for more information: Carl@Stertil-Koni.com | tel 336.314.8600

Discover the ultimate Freedom of Choice in heavy duty vehicle lifting systems, comprehensive shop equipment, and lift accessories. Our experts are ready to help. For a free quote, contact us today.



DISTRIBUTED BY

200 Log Canoe Circle | Stevensville, MD 21666 tel 410.643.9001 or (toll free) 800.336.6637 | fax 410-643-8901 | email lifts@stertil-koni.com Find a local distributor at https://stertil-koni.com/distributors